


Blachowkręty z łem walcowym wypukłym z gniazdem krzyżowym



Cross recessed pan head tapping screws
Linsen-Blechschauben (Form C)
ISO 7049
PN/M 83116

d	2,2 No. 2	2,9 No. 4	3,5 No. 6	3,9 No. 7	4,2 No. 8	4,8 No. 10	5,5 No. 12	6,3 No. 14
/ w mm (calach)								
6,5 (1/4")	+	+	+	+				
9,5 (3/8")	+	+	+	+	+	+		
13 (1/2")	+	+	+	+	+	+	+	+
16 (5/8")	+	+	+	+	+	+	+	+
19 (3/4")	+	+	+	+	+	+	+	+
22 (7/8")	+	+	+	+	+	+	+	+
25 (1")	+	+	+	+	+	+	+	+
32 (1 1/4")		+	+	+	+	+	+	+
38 (1 1/2")			+	+	+	+	+	+
45 (1 1/4")			+	+	+	+	+	+
50 (2")			+	+	+	+	+	+
60 (2 3/8")				+	+	+	+	+
70 (2 3/4")				+	+	+	+	+
80 (3 3/8")					+	+	+	+
90 (3 1/2")						+	+	+
100 (4")						+	+	+
120 (4 1/2")						+	+	+
sztuk w opakowaniu	1000	1000	1000	1000	1000	1000	1000	500
			od 45	od 38	od 32	od 25	od 25	od 25
			500	500	500	500	500	200
					od 50	od 45	od 45	
					200	200	200	
r _f =	3,4	4,4	5,4	5,8	6,2	7,2	8,2	9,5
k _{max}	1,8	2,2	2,6	2,8	3,05	3,55	3,95	4,55
d _{k max}	4,2	5,6	6,9	7,5	8,2	9,5	10,8	12,5

oferta firmy dotyczy pól oznaczonych "+"